



ALL IN ONE SILENT RECIPROCAL AIR COMPRESSOR

- Combine pressure vessel, refrigerate dryer, and reciprocal compressor as a complete compressed air system, saving configurations on extra piping and wiring, and space for installation.
- Package includes low oil protection, overload protection, automatic water drains on both dryer and tank, Dual control, Timer controlled auto shut off after idle, sensor controlled ventilation fans, hour meter, and maintenance schedule notification.
- Cabinet design reduces noise level as well as dust accumulation around key components.
- Reciprocal compressors allow easy maintenance and self-services thus reducing operation costs.
- Single stage (6.5HP) and two stage (6.5 & 7.5HP) compressors are available.
- Optional remote monitoring available.



SS65087-D



ST65087-D



ST75087-D

| MODEL | | SS65087-D | ST65087-D | ST75087-D |
|------------------------------|----------------|--------------------------|--------------------------|------------------------|
| Electric Motor | HP | 6.5 | 6.5 | 7.5 |
| | RPM | 3550 | 3550 | 1730 |
| | Volt/Phase/Amp | 208-230/single/32.8-39.3 | 208-230/single/32.8-39.3 | 208-230/single/35.5-40 |
| Pump R.P.M | | 1180 | 1100 | 865 |
| Max. Working PSI | | 140 | 175 | 175 |
| C.F.M. | @40 PSI | 26 | — | — |
| | @90 PSI | 23 | 20 | 23 |
| | @175 PSI | — | 18 | 21.8 |
| TANK | Gal | 86.8 | 86.8 | 86.8 |
| | Style | Horizontal | Horizontal | Horizontal |
| | Code | ASME | ASME | ASME |
| Weight (lbs.) | | 850 | 990 | 1110 |
| L x W x H (in) | | 72 x 26 x 64 | 73 x 30 x 72 | 73 x 30 x 72 |
| Rising / recovery time (sec) | | 340/60 | 475/90 | 385/52 |
| Noise (dB) | | 70 | 69 | 68 |

PUMA INDUSTRIES, INC.

1992 Airways Blvd. Memphis, TN 38114
 TEL:1-901-744-7979 FAX:1-901-744-7579
 e-mail:sales@pumaaircenter.com
 http://www.pumaairusa.com



★ These products are protected by one or more patents. Others may be pending.
 ★ All products functions may re-design or be changed without notice.